call barge in to specific DDI's using chanspy

|--|

In order to setup call barge in, you will need to follow the below steps

First, enable chanspy in modules > feature codes, and then select the extension you want.

ChanSpy	555	Customize	Enabled

Then go to modules > config edit, you are looking for extensions_custom.conf

· Milacis configuration file Eultor

+ Add New File	
- 🗅 Asterisk Custom Configuration Files	
- 🗅 ari_additional_custom.conf	
— 🗅 ari_general_custom.conf	
— 🗅 ccss_general_custom.conf	
- 🗅 cel_custom_post.conf	
— 🗅 cel_general_custom.conf	
- 🗅 cel_odbc_custom.conf	
- 🗅 confbridge_custom.conf	
extensions_custom.conf	
—	
- 🖹 extensions_custom_asternic_outbound_freepbx_failover.conf	
— D features_applicationmap_custom.conf	
— D features_featuremap_custom.conf	
— [] features_general_custom.conf	
— 🖹 freepbx_menu.conf	
_ I freepbx_module_admin.conf	
— D globals_custom.conf	
- 🗅 http_custom.conf	
- 🗅 iax_custom.conf	-

If you go into this file, you want to paste the below code and remove or add what you want in order to block barge in on particular ddi's.

[ext-local-custom] ; Block Access exten => _*2227760,1,Macro(user-callerid,) exten => _*2227760,n,Hangup exten => _*2237760,1,Macro(user-callerid,) exten => _*2237760,n,Hangup exten => _*2247760,1,Macro(user-callerid,) exten => _*2247760,n,Hangup exten => _*2227761,1,Macro(user-callerid,) exten => _*2227761,n,Hangup exten => _*2237761,1,Macro(user-callerid,) exten => _*2237761,n,Hangup exten => _*2247761,1,Macro(user-callerid,) exten => _*2247761,n,Hangup exten => _*2227721,1,Macro(user-callerid,) exten => _*2227721,n,Hangup exten => _*2237721,1,Macro(user-callerid,) exten => _*2237721,n,Hangup exten => _*2247721,1,Macro(user-callerid,) exten => _*2247721,n,Hangup ; Listen exten => _*222x.#,1,Macro(user-callerid,) exten => _*222x.#,n,Answer exten => _*222x.#,n,NoCDR

exten => _*222x.#,n,Wait(1) exten => _*222x.#,n,ChanSpy(sip/\${EXTEN:4},q) exten => _*222x.#,n,Hangup ; Whisper exten => _*223x.#,1,Macro(user-callerid,) exten => _*223x.#,n,Answer exten => _*223x.#,n,NoCDR exten => _*223x.#,n,Wait(1) exten => _*223x.#,n,ChanSpy(sip/\${EXTEN:4},qw) exten => _*223x.#,n,Hangup ; Barge In exten => _*224x.#,1,Macro(user-callerid,) exten => _*224x.#,n,Answer exten => _*224x.#,n,NoCDR exten => _*224x.#,n,Wait(1) exten => _*224x.#,n,ChanSpy(SIP/\${EXTEN:4},qB) exten => _*224x.#,n,Hangup

Note you want to change the *222, *222, *223 and *224 to the code you wish to dial when doing the barge in.

Posted by: Keira Tait - Fri, Apr 27, 2018 at 2:30 PM. This article has been viewed 3192 times.

Online URL: https://kb.ic.uk/article/call-barge-in-to-specific-ddi-s-using-chanspy-204.html (https://kb.ic.uk/article/call-barge-in-to-specific-ddi-s-using-chanspy-204.html)